
48-Port CAT 6 High Density Feed-Thru Patch Panel

PRODUCT SPECIFICATION

Package includes:

A. 48-Port Feed-Thru Patch Panel w/Couplers, 1 pc
B. #12-24 x 5/8" Pan Head, Pilot Point Machine Screw, 4 pcs





Features and Benefits:


- Rack mounted reinforced steel panel with pre-numbered ports
- Flush mount design adds stability by allowing a rigid fit and a neat finished appearance
- Designed to support the distribution of voice, data, and audio needs for commercial or residential applications
- Plug and play solution for easy installation
- Designed to fit all standard 19" racks and cabinets
- 1 rack mount space (RMS)

PATCH PANEL, CAT 6, FEED-THRU 48-P,1RMS				ICC
ITEM NO.	ICMPP48C61	REV.	A	PremiumProducts ProvenPerformance CompetitivePrices
DWG NO.	PSMPP48C61	PAGE NO.	1	

CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com







FREQUENCY (MHz)	NEXT (dB)	RETURN LOSS (dB)	ACRF (dB)	INSERTION LOSS (dB)
10.00	56.6	19.0	43.3	6.3
100.00	39.9	12.0	23.3	21.3
200.00	34.8	9.0	17.2	31.5
250.00	33.1	8.0	15.3	35.9

NOTE: UNLESS OTHERWISE SPECIFIED

1. BLANK PATCH PANEL:
   A. MATERIAL: 16 GA CRS
   B. SURFACE FINISH: BLACK POWDER COAT
2. CAT 5E COUPLER:
   - ELECTRICAL:
   A. CURRENT RATING: 1.5 AMPS MAX
   B. VOLTAGE RATING: 150 VOLTS ALTERNATING
   C. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VOLTS RMS, 60 HZ
   D. INSULATION RESISTANCE: > 10 MOHMS
   - MECHANICAL:
   A. MATING FORCE: 5 LBS MAX
   B. UNMATING FORCE: 5 LBS MAX
   C. PLUG RETENTION IN JACK: 20 LBS MIN
   D. DURABILITY: 750 CYCLES
   - MATERIAL & FINISH:
   A. HOUSING: ABS, UL 94V-0
   B. COLOR: BLACK
   C. CONTACT: PHOSPHOR BRONZE GOLD PLATING OVER 100 MICRO INCH NICKEL
   D. GOLD PLATING: 1.27 MICRON/50 MICRO INCH MIN

WIRING DIAGRAM	
PIN	PIN
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8

PATCH PANEL, CAT 6, FEED-THRU 48-P,1RMS

ITEM NO.	ICMPP48C61	REV.	A
DWG NO.	PSMPP48C61	PAGE NO.	2

*Premium***Products** *Proven***Performance** *Competitive***Prices**